



## Haulette HA16PX

## Rough Terrain Articulating Boom

### Technical Data

Working height	16 m
Platform height	14 m
Horizontal outreach	9.15 m
Up and over clearance	6.6 m
Lift capacity	230 kg
Platform size (F x G)	1.8 x 0.8 m
Length (A)	6.95 m
Transport length	5.25 m
Width (B)	2.3 m
Height - stowed (C)	2.3 m
Transport height	2.6 m
Vertical jib rotation	140° (+70/-70)
Platform rotation	180° (+90/-90)
Turntable rotation	360°
Tailswing	0 m
Wheelbase (D)	2m
Ground clearance (E)	40 cm
Tilt	5°
Drive speed	0.8 - 5.5 km/h
Gradeability	50 %
Turning radius - outside	3.75 m
Tires - foam-filled	385/65-22.5
Power source	31 kW- 42 hp
Hydraulic system capacity	100 l
Fuel tank capacity	72 l
Weight	6950 kg

### Standard Equipment

- 4 wheel drive and steer
- Continuous 360° turntable
- Safe to use in winds up to 60km/h
- Swing out engine tray for ease of maintenance
- 72 l fuel tank; 1.50 m filling height
- 5° tilt alarm
- 12 V battery / electrical control system
- Auxiliary power in the platform for emergency descent
- Brake release
- Hourmeter
- Mechanical turret slewing hook
- Towing hooks / lifting eyes

### Options and Accessories

- 3.3 kW on-board generator
- Power to platform
- Large basket 2.3 x 0.80 m
- Travel alarm
- Rotating beacon
- Working light
- Catalytic exhaust
- Biodegradable hydraulic oil
- Cold Weather Package
- Warm environment kit
- Air line in platform



**comarco**

Combining Experience, Know-How & Equipment

# Haulette HA16PX

## Rough Terrain Articulating Boom

